



Semi-scissor platform lift

HDS25 Single

article no.: HDS25xxxxxF02

The HDS25 heavy duty semi-scissor lift with a capacity of 25 t is available with different platform lengths from 6.5 m up to 14.5 m. This platform lift is suitable for a multitude of commercial vehicles and has been approved in many different applications so far. The recessed version of the lowered lift is level with the floor and can be crossed over with vehicles. The floor



Semi-scissor platform lift HDS25 Single

PAGE 2/4

version does not require any constructional measures and can be quickly installed anywhere.
In all cases, you remain flexible and make optimum use of your workshop surface.



specifications

article no.		HDS25xxxxxF02
load support	load support	platforms
	capacity	25 t
	quantity of platforms	2
	width of platforms (mm)	750 mm
	height of platforms (mm)	360 mm
	distance between platforms	1100 mm
	platform surface	smooth metal sheet
lifting height	lifting stroke effective	1750 mm
	lifting height / floor version	2140 mm
	lifting height / recessed version	1780 mm
speed	lifting time	90 sec.
	lowering time (under load)	90 sec.
drive	mode of drive	electro-hydraulic
	motor	AC voltage
	motor power (kW)	8.8 kW
power supply	type of power supply	mains supply
	electrical connection	400V/3Ph+N+PE/50Hz
	compressed air connection	6 bar
	fuse (Amps)	32 A
operation	mode of operation	1 central control unit
	control	electronic
	Softstart	X
regularisation	synchronisation	proportional valves, infinitely variable
load securing	load securing	hydraulic and mechanical
protection class		IP65
floor load	quality of foundation	C20/25
surface treatment	type of surface treatment	powder coating
	colour	grey RAL7015



accessories



HDSF07-ST02

Electric sockets 230V



HDSF07-DL02

Pneumatic sockets




HDSF07-BL-LED04

4 LED lamps



HDSF07-BL-LED06

6 LED lamps



HDSF07-BL-LED08

8 LED lamps



HDSF07-BL-LED10

10 LED lamps



HDSF07-AS01

anti-skid surface anti-skid class
R13



HDSF07-AS02

anti-skid surface anti-skid class
R13




HDSF0713-235

2 ascending ramps, 2350 mm



HDSF0713-330

2 ascending ramps, 3300 mm



HDSF0713-180H

2 ascending ramps, hanging,
1800 mm



HDSMHFL160-200-F07

jacking beam 16 t, pneumatic



HDSF07BA-XXXXX

floor levelling for pits of plat-
forms



HDSF07FV-XX

Galvanizing



HDSF07DUROPLEX-XX

Special coating in addition to
galvanizing



HDSF07-SK01

2. control box in the washing
area

