

Electro-hydraulic workshop presses with single acting cylinder 40 - 60 ton

Single acting cylinder: One-way pressing action for where heavy tooling is not to be mounted on the piston.



13 14



	Model	Max (Ton)	(mm/ sek)	(Pull/ ton)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	I (mm)	Kg	Kw
13	EP 40	40	9,0	-	840	840	200	300	125	60	1830	1450	620	345	2,2
14	EP 60	60	10,0/5,0	-	850	1000	255	300	160	80	1980	1760	680	670	2,2
15	EP 40 D	40	9,0	6	810	840	200	300	125	60	1940	1450	620	355	2,2
16	EP 60 D	60	10,0/5,0	6	820	1000	255	300	160	80	1980	1640	680	717	2,2
17	EP 100 D	100	10,0/1,4	4	900	1025	300	320	220	100	2150	1620	860	910	2,2

EP 40 D = Electro hydraulic Press.

EP 40 D = Capacity 40 tons.

EP 40 D = Double acting cylinder.

Electro-hydraulic workshop presses with double acting cylinder 40 - 100 ton

 **Double acting cylinder:**
Featuring both pressing and pulling facilities.



Accessories

61100



Press plate.



Press punches.
(7 pieces, Ø12, 14, 16,
20, 22, 25, 30)



Winch
for EP 100 D.
(Factory mounted)

